

32:9 Ultra Stretch for Dynamic Digital Content

Ultra Stretch Signage 88BH7D



88BH7D is a totally new signage format with a 32:9 widescreen and Ultra HD resolution. It can display eye-catching content dynamically, utilizing existing spaces and maximizing the interior effects thanks to its unique ratio. This product—a work of art in itself—promotes the value of spaces.




Key Features

New Design Configuration



Ultra HD Resolution (3,840 x 1,080)

Ultra HD large screens deliver an immersive viewing experience.



32:9 Extended Wide Format

Dynamic content is delivered on one screen thanks to the new widescreen-format 32:9 bar-type display.



Sleek Design for Space

The Ultra Stretch Signage delivers seamless content as a in-store signboard or digital banner with its unique ratio. It maximizes both interior and advertisement effects, when installed in remaining or existing spaces, such as on a wall, pillar, or above the entrance.



Download LG Commercial Display Mobile App



Learn more www.lg.com/b2b

YouTube youtube.com/c/LGCommercialDisplay

LG may make changes to specifications and product descriptions without notice.
Copyright © 2017 LG Electronics Inc. All rights reserved. "LG Life's Good" is a registered trademark of LG Corp.
The names of products and brands mentioned here may be the trademarks of their respective owners.



32:9 Ultra Stretch for Dynamic Digital Content

Ultra Stretch Signage 88BH7D



Screen Size
88"

- 88BH7D
- Brightness: 700 cd/m²
 - Aspect Ratio: 32:9
 - Bezel: 4.4 mm (L/R), 5.9 mm (T/B)
 - Depth: 103.9 mm
 - Interface: HDMI (3), DP, RJ45, IR, USB (2), SD Card, RS232C



Other Features

Multiple Screens



PBP with Four Divisions in Landscape or Portrait

The Picture-by-Picture (PBP) feature allows you to divide a screen into as many as four parts, in landscape or portrait installations. It is a very effective and convenient way to deliver several advertisements or pieces of information at the same time.



Content Management



32:9 Content Editing

With the LG SuperSign Media Editor, you can easily edit images or video clips of original content to fit 32:9 ratio.



Still Image or Video

Edited Still Image or Video

Multiple Content Creation

Users can edit content that consists of one video and several still images (up to 20) as they want.




Support 1 Video + 20 Images

Convenient Connectivity Support



Tiling Scene with Daisy Chain

This product supports lateral tiling for 1x4 or 4x1 installations (landscape or portrait), and up to a 4x4 installation with a daisy chain configuration.



LAN Daisy Chain

The LAN daisy chain allows you to control and monitor devices, distribute content, and even update firmware.




Specifications

		88BH7D
PANEL	Screen Size	88"
	Panel Technology	IPS
	Aspect Ratio	32:9
	Native Resolution	3,840 x 1,080 (UHD)
	Brightness	700 cd/m ² (Typ)
	Contrast Ratio	1,100:1 (Typ)
	Dynamic CR	500,000:1 (Typ)
	Viewing Angle (H x V)	178 x 178
	Color Depth	10bit(D), 1.07 Billion
	Response Time	8ms (G to G BW) typ.
	Surface Treatment	AGLR (Haze 3%)
CONNECTIVITY	Orientation	Landscape & Portrait Mode
	Input	HDMI (3), DP, OPS, DVI-D, Analog Audio, USB 2.0, USB 3.0, SD Card
	Output	DP, Analog Audio
	External Control	RS232C In/Out, RJ45 In/Out, IR & Light Sensor, Pixel Sensor
PHYSICAL SPECIFICATION	Bezel Color	Black
	Bezel Width	4.4 mm (L/R), 5.9 mm (U/D)
	Monitor Dimension (W x H x D)	2,158.3 x 611.2 x 103.9 mm
	Weight (Head)	34.2 kg
	Carton Dimensions (W x H x D)	2,274 x 717 x 212 mm
	Packed Weight	53.2 kg (Pallet included)
	Handle	Yes
SPECIAL FEATURES	VESA™ Standard Mount Interface	600 x 400 mm
		Temperature Sensor, Auto Brightness Sensor, Tile Mode, Natural Mode@Tile Mode, ISM Method, DPM Select, Energy Saving, Smart Energy Saving, File Play with USB/SD/Internal Memory, 2/3/4PBP, Internal Memory 8GB (System 4GB + Available 4GB), Wi-Fi Dongle Ready(Support Beacon function), 4K Up Scaling
ENVIRONMENT CONDITIONS	Operation Temperature Range	0 °C to 40 °C
	Operation Humidity Range	10 % to 80 %
POWER	Power Supply	100-240V~, 50/60Hz
	Power Type	Built-In Power
	Power Consumption	Typ. / Max. 400 W / 500 W
		Smart Energy Saving 30% of typical
STANDARD (CERTIFICATION)	Safety	UL / cUL / CB / TUV / KC
	EMC	FCC Class "A" / CE / KC
	ErP / Energy Star	Yes / No
MEDIA PLAYER COMPATIBILITY	OPS PC compatible (optional)	Yes
	External Media player Attatchable	No
SOFTWARE COMPATIBILITY	Content Management Software	SuperSign Premium
	Control and Monitoring Software	SuperSign C
ACCESSORIES	Basic	Remote Controller (including battery 2ea), Power Cord, DP (2.6M), RS-232C Cable (3M), Owner's Manual (Website upload)
	Optional	AN-WF500 (Wi-Fi USB Dongle), MP700, KT-OPSA (OPS KIT), KT-SP0 (RGB Sensor) ** Stand is not available

Dimension (unit : mm)

88"

2,158.3 x 611.2 x 103.9 mm / 34.2 kg



Connectivity

- 1 IR & LIGHT SENSOR
- 2 RS-232C In
- 3 RS-232C Out
- 4 AUDIO In
- 5 AUDIO Out
- 6 DP Out
- 7 DP In
- 8 RS-232C In
- 9 HDMI 1.4
- 10 HDMI 2.0
- 11 USB 2.0
- 12 USB 3.0
- 13 SD Card
- 14 LAN In
- 15 LAN Out
- 16 Pixel Sensor

